

SWITCH / DEVICE SELECTOR

		APPLICATION								DMSS
		PRIMARY DRAIN LINES ONLY	PRIMARY DRAIN LINE OR PRIMARY DRAIN PAN (AUXILIARY OUTLET)	PRIMARY DRAIN PAN (AUXILIARY OUTLET) ONLY	PRIMARY DRAIN PAN (AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES)	PRIMARY DRAIN LINE (OR AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES)	SECONDARY DRAIN PAN ONLY	PRIMARY & SECONDARY DRAIN PANS (2 PROBES)	PRIMARY OR SECONDARY DRAIN PANS	
DEVICE	PATENT									
SS1 [†]	10,406,570	✓								
SS1P ^{†*}	10,406,570	✓								
SS2				✓						
SS2P [†]				✓						
SS3	6,698,215						✓			
SS3P [†]	6,698,215								✓	
EZT205 (contains trap)		✓								
EZT210 (contains trap)		✓								
EZT224				✓						
EZT225			✓							
EZT226				✓						
EZT228			✓							
EZT230		✓								
AG1100+ (metal only)	7,710,283						✓			
AG1200+	7,710,283						✓			
AG4200M [†] (drain outlet)	7,878,019 • 8,317,169						✓			
Electronic										
AG1250E	8,578,770						✓			
AG3125E	8,151,580 • 8,561,417 • 8,578,770			✓						
AG3150E [†]	8,151,580 • 8,561,417 • 8,578,770 • 7,774,395				✓					
AG3175E ^{†*}	8,151,580 • 8,561,417 • 8,578,770 • 7,774,395				✓					
AG3180E ^{†*}								✓		
AG4200E [†] (drain outlet)	8,578,770 • 8,317,169 (for vibration isolators)						✓			
SS103E [†] (primary drain line + aux pan / aux outlet + aux pan)					✓	✓				
SS500EP [†]	Patent Pending								✓	
SS610E	8,887,392									✓
SS700E	Patent Pending						✓			
SSW	Patent Pending						✓			
Cleanout										
SC1	10,406,570	✓								

[†] Also a cleanout device
[◦] Plenum rated

[^] RectorSeal Goliath, Titan & Spartan drain pans only
^{*} Able to handle 2 probes

SWITCH / DEVICE FEATURES

Mechanical														
DEVICE	SENSOR TYPE		SWITCH TYPE		SENSING TECHNOLOGY		SUPPLY VOLTAGE	SWITCHING VOLTAGE	SWITCHING CURRENT			SWITCHING LOGIC		
	FLOAT	REED	MICROSWITCH	BUOYANCY/MAGNET	BUOYANCY	NOT NEEDED	0-24V	0 – 1.25 AMP (carry current, UL rating) 0 – 0.5 AMP (switching current)	0 – 4 AMP	0 – 5 AMP	NORMALLY CLOSED (NC)	NC ONLY w/NO Capability	NC / NO	
SS1	✓	✓		✓		✓	✓	✓			✓			
SS1P	✓	✓		✓		✓	✓	✓			✓			
SS2	✓	✓		✓		✓	✓	✓			✓			
SS2P	✓	✓		✓		✓	✓	✓			✓			
SS3	✓	✓		✓		✓	✓	✓			✓			
SS3P	✓	✓		✓		✓	✓	✓			✓			
EZT205	✓		✓		✓	✓	✓		✓			✓		
EZT210	✓		✓		✓	✓	✓		✓			✓		
EZT224	✓		✓		✓	✓	✓		✓			✓		
EZT225	✓		✓		✓	✓	✓		✓			✓		
EZT226	✓		✓		✓	✓	✓		✓			✓		
EZT228	✓		✓		✓	✓	✓		✓			✓		
EZT230	✓		✓		✓	✓	✓		✓			✓		
AG1100	✓		✓	✓		✓	✓			✓			✓	
AG1200	✓		✓	✓		✓	✓			✓			✓	
AG4200M	✓		✓	✓		✓	✓			✓			✓	

Electronic									
DEVICE	SENSOR TYPE	SWITCH TYPE	SENSING TECHNOLOGY	SUPPLY VOLTAGE		SWITCHING VOLTAGE		SWITCHING CURRENT	SWITCHING LOGIC
	METAL PINS/PROBE	RELAY	WATER RESISTANCE	24VAC	110 – 230VAC	0 – 24V	0 – 250V	0 – 5 AMP	NC / NO
AG1250E	✓	✓	✓	✓		✓		✓	✓
AG3125E	✓	✓	✓	✓		✓		✓	✓
AG3150E	✓	✓	✓	✓		✓		✓	✓
AG3175E	✓	✓	✓	✓		✓		✓	✓
AG3180E	✓	✓	✓	✓		✓		✓	✓
AG4200E	✓	✓	✓	✓		✓		✓	✓
SS103E	✓	✓	✓	✓		✓		✓	✓
SS500EP	✓	✓	✓	✓		✓		✓	✓
SS610E	✓	✓	✓		✓		✓	✓	✓
SS700E	✓	✓	✓	✓		✓		✓	✓
SSW	✓	✓	✓	✓		✓		✓	✓